

DREAM CLICK PRO

914,4 x 152,4 x 5,3 mm - 36" x 6" x 0.20"
15 planks/box = 2,09 m² (16,43 kg) = 22.49 sq ft (36.81 lb)
63 boxes/pallet = 131,67 m² (1057 kg) = 1,416.87 sq ft (2,354 lb)

Product specification

Total thickness	EN 428	5,30 mm / .20 inches
Wear layer	EN 429	0,55 mm / 22 MIL
Total weight	EN 430	8 kg/m ² (.5lbs/ft ²)
Surface treatment		PUR
Usage classification	EN 685	23 - 33 - 42

Test results

Underfloor heating	EN 12524	suitable - max. 27° (80°F)
Castor chair	EN 425	pass
Fire resistance	EN 13501-1	Bfl-s1
Coefficient of Friction	ASTM C1028	0.77 Dry 0.69 Wet
Durometer Hardness	ASTM D2240	97
Static load limit	ASTM F970	pass (1,500 Lbs)
Electrical resistance	ASTM F150	resistant
Radiant Flux	ASTM 648	class 1 (0.54 watts/cm ²)
Dimensional stability	ASTM F 2199	pass
Flexibility	ASTM F137	pass (6 mm)
Impact resistance	ASTM F1265	pass
Resistance to heat	ASTM F1514	pass
Resistance to light	ASTM F1515	pass
Size and squareness	ASTM F2055/F2421	pass
Abrasion Resistance	ASTM D4060	60,000 cycles
Chemical resistance	EN 423 / ASTM F925	OK / No Effect 24 hrs
Residual indentation	EN 433 / ASTM F1914	< 0,10 mm / 0.009 (4%)
Slip resistance	DIN 51130 EN 13983	R10 class DS
Sound reduction	EN ISO 717-2 (ΔLw)	8 dB
Light fastness	ISO 105-B02	> 6
Drum noise	EPLF	SL60
Locking strength		500 kg/m - 340 lbs/lin ft
Anti static	EN 1815	yes
Residential warranty		Lifetime
Commercial warranty		10 years
Formaldehyde		E1



Distributed by:

Wood Culture Pte Ltd (A Wholly Owned Subsidiary of Hafary Holdings Limited)

A: 11 Changi North Way S498796
T: +65 6686 2133

E: sales@woodculture.com.sg
W: www.woodculture.com.sg

facebook.com/woodculturepteltd
instagram.com/wood_culture_